

## KN110, KN150, KN200 Mobile safety shower & eyewash (insulated and jacket)

The MB 28 mobile Emergency Safety Station with body shower or drench shower including eyewash or facewash. It is easy to transport on wheels, with stainless steel tank and frame. The system is under air pressure and guarantees a long-lasting good spraying pattern. The cylinder tank is made of stainless steel (including sign). The cylinder is covered with a HDPE jacket and is insulated and in this way the unit has protection against solar energy.

The body shower has a special shower head (spray angle 60° and gives rotation to the water) for an effective and efficient flushing. The eyewash is made of ABS bowl and hinged lid (including sign). The lid is at the same time the operation of the eyewash (pull forward and the water starts flushing). When the lid is pushed back and closed the eyewash automatically stops. Because of this hinged lid the eyewash remains clean and hygienic. The eyewash is equipped with diffusers (optional supplemented with black rubber eye cups). These diffusers give a gentle aerated soft spray pattern which feels pleasant for your eyes. A drain is present on the bowl. The standard flush time of the eyewash is 12,5 minutes, depending on different shower heads the flushing duration can be made longer.

The operation of the body shower is operated by the operation handle / lever. The standard spray time of the body shower is 4 minutes, depending on different shower heads the duration can be made longer. The unit is equipped with eyewash. As an optional fitting an extra hand held eyewash can be added to the unit with one or two spray heads/ diffusers. The eyewash heads has dust covers on the diffusers optional supplemented with black rubber eye cups with hinged dust covers (including sign). The diffusers gives a gentle aerated soft spray pattern which feels pleasant for your eyes.

### OPTIONAL FITTINGS

Heater frost protection possibility, towing hitch, hand-held eyewash, double (two) diffusers, black rubber eye cup with hinged dust cover.

### DIMENSIONS AND TANK DETAILS

<b>Model no.:</b> KN110	Width: 765 mm
<b>Tank size:</b> 120L	Height: 2250 mm
<b>Weight:</b> 70 kg (empty)	Depth: 1550 mm
(weight is without optional fittings and water)	

<b>Model no.:</b> KN150	Width: 765 mm
<b>Tank size:</b> 150L	Height: 2250 mm
<b>Weight:</b> 85 kg (empty)	Depth: 1550 mm
(weight is without optional fittings and water)	

<b>Model no.:</b> KN200	Width: 785 mm
<b>Tank size:</b> 200L	Height: 2250 mm
<b>Weight:</b> 100 kg (empty)	Depth: 1550 mm
(weight is without optional fittings and water)	



Manufactured in accordance to ANSI Norm Z358.1- latest edition and SS-EN 15154-1 & 2:latest edition.