

Firefighting monitor AKRON Forestry 3462



Reference: 34487
EAN13: -

Product features:

Material: Pyrolite
Max. flow: 1365 L/min (300 GPM)
Amplitude of elevation: +90° / -45°
Amplitude of elevation: +45° / -20°
(adjustable stops)
Rotation amplitude: 320°
Rotation amplitude: stops adjustable to ±90
Dimensions (WxHxD): 294 x 335 x 226 mm
Power supply: 24 V
Flow range: 115 - 230 - 360 - 475 L/min (head supplied)
Weight: 10.4 kg (monitor only)
Weight: 12.7 kg (with head)
Inlet (diam. / thread): 2" NPT (Female)
Output (diam. / thread): 1.5" (male)
Set includes :: FireFox head 32930001
Set includes :: Monitor Forestry 3462
Set includes :: CAN proportional joystick
Set includes :: Connection cable (6 m)

Firefighting monitor AKRON Forestry 34622100: a portable, robust, high-performance solution for fighting forest fires, brush fires and fires in remote areas.

This **portable 24 V motorized monitor**, made of **Pyrolite®** for optimum lightness, is designed for harsh environments. Its proportional CAN joystick control enables precise positioning of the water or foam jet, even in steep or difficult-to-reach terrain.

Key benefits

- **Pyrolite® material:** corrosion- and impact-resistant composite alloy, with reduced weight (? 10.4 kg without head).
- **24 V motorization:** motorized rotation up to 320° and elevation from -20° to +45°, ensuring wide intervention coverage.
- **Proportional CAN joystick control:** smooth, intuitive handling for rapid deployment.
- **Interchangeable heads:** compatible with AKRON 3293 series models (fixed or variable flow jets).

Equipment included with reference 34622100

- Monitor 24 V motor with integrated control harness.
- Adjustable **low-flow head** (? 115 to 475 L/min), model 3293.

- CAN control joystick with 6 m cable.
- IP67 waterproof connectors with secure locking.

Available options

- 12 V version (ref. AKRON 34621100).
- Series 3293 low-flow, medium-flow and fixed-flow heads.
- Foam options: foam tube Quick Attack type, CAFS injectors.
- Motorized valves, quick connectors, spray heads.
- CAN-compatible wireless remote control.

Fields of application

- Fighting vegetation, brush and forest fires.
- Protection of rural areas, campsites, isolated infrastructures.
- Equipment on all-terrain vehicles, trailers or mobile intervention units.
- Use with CAFS (Compressed Air Foam System).

Technical specifications

Features	Description
Reference	AKRON 34622100
Material	Pyrolite®
Rotation	320°, ± 90° stops
Elevation	-20° à +45°
Weight	? 10.4 kg (without head)
Control	Proportional CAN joystick (with 6 m cable)
Protection class	IP67
Compatible heads	AKRON 3293 : <ul style="list-style-type: none">• 115-230-360-475 L/min• 475-660-950-1140 L/min• Fixed-flow diffused jet (please specify)

MMF Protection et Sécurité expertise at your service

As an **official reseller and authorized repair center AKRON® in France**, **MMF Protection et Sécurité** offers you this monitor with full support: purchasing advice, technical documentation, assistance with integration on your vehicles or trailers, maintenance and original spare parts.

Our technical team will help you identify the ideal configuration (flow rate, head type, control) to suit your field constraints. Don't hesitate to contact us for a personalized quote or technical advice.

