

## Marine-approved SOLAS heavy-duty discharge fire hose



### SOLAS/MED marine-certified discharge hose

This **heavy-duty fire hose** is designed to meet the demands of the marine sector. **MED-certified (Marine Equipment Directive)** and compliant with international standards (DIN 14540, BS 6391:2008 Type 1, Pr EN 1924 Class 1), it offers maximum safety for operations both at sea and on land.

Its high-tenacity polyester textile weave and SBR/NBR rubber inner lining ensure excellent resistance to hydrocarbons, ozone and the elements. The perfectly smooth inner wall considerably reduces pressure loss.

### Technical specifications

- Available diameters: 25 mm (1"), 38 mm (1½"), 42 mm, 45 mm (1¾"), 52 mm (2")
- Operating pressure: 17 to 20 bar (depending on diameter)
- Burst pressure: up to 60 bar
- Max. longitudinal/transverse elongation : 3 %
- Operating temperature: -30°C to +80°C
- Weight: 140 to 280 g/m depending on diameter
- Wall thickness: 1.3 to 1.5 mm
- Standard lengths: 20 m and 40 m (others on request)
- Options: tied DSP fittings, carrying strap

### Benefits

This hose is renowned for its **resistance to abrasion, ageing and chemical agents**. Light and flexible, it is easy to store thanks to its small winding diameter, and maintenance is simple with quick drying. It can also be repaired (kits available on request).

### Areas of use

- Merchant marine and shipping (SOLAS/MED approval)
- Fire department and civil protection
- Industry and refineries
- Agriculture and irrigation
- Public works

## Distribution MMF Protection et Sécurité

Available from **MMF Protection et Sécurité** this fire hose is the ideal solution for demanding marine and industrial environments. Reliable, certified and built to last.