

PIL 3-piece aluminum clamp



3-piece aluminum PIL clamp

The **symmetrical D.S.P ET A.R NF S 61-701-PN25 fitting**, with its **3-piece aluminum PIL clamp**, is designed to ensure a reliable and secure connection in hydraulic and industrial installations. This product is manufactured to NF S 61-701 standards, guaranteeing its resistance and durability in demanding environments.

The fitting is available in a symmetrical version, making it easy to install and maintain. It is ideally suited to high-pressure use, with a PN25 capacity, enabling optimum working conditions for most hydraulic systems.

The aluminum PIL clamp is an essential component of this fitting, designed to guarantee optimum clamping and secure attachment, even in the most demanding environments. Aluminum, renowned for its light weight and corrosion resistance, makes it the perfect choice for long-lasting industrial applications.

Features :

- Standard: Complies with NF S 61-701, guaranteeing optimum quality and maximum safety.
- Pressure: PN25, withstands high pressures for robust industrial and hydraulic applications.
- Material: Lightweight, corrosion-resistant 3-piece aluminum PIL clamp.
- Connection type: Symmetrical D.S.P ET A.R., offering ease of installation and maintenance.
- Applications: Ideal for hydraulic and industrial installations where strength and reliability are essential.
- Size: Available in several sizes to suit different installation requirements.

Advantages of PIL 3-piece aluminum clamps:

Simplified installation: Thanks to its symmetrical design, the fitting is easy to install, reducing on-site work time.

High resistance: PN25 standard ensures high pressure resistance, enabling use in high-stress environments.

Lightweight yet robust: The aluminum clamp offers an excellent compromise between lightness and strength, while being highly resistant to corrosion.

Standards-compliant: The fitting complies with NF S 61-701 standards, ensuring that installation meets safety and performance requirements.



Durability: The product is designed to withstand harsh working conditions, offering increased installation longevity.

Application:

This symmetrical fitting and clamp are essential for ensuring the efficiency and safety of industrial and hydraulic installations. It is ideal for :

- Water and industrial fluid distribution systems requiring high pressure.
- Hydraulic networks in environments where long-term reliability is crucial.
- Maintenance applications where ease of installation and dismantling is an asset.

The clamp's aluminum construction also enables installation in areas exposed to corrosion without loss of performance. Suitable for both indoor and outdoor use.

The **D.S.P ET A.R NF S 61-701-PN25 symmetrical connector with aluminum PIL clamp** is the perfect choice for those looking for a high-quality product that's easy to install, durable and reliable. Whether you're in industry, maintenance or infrastructure management, this fitting will enable you to guarantee the safety and performance of your installations.

For further information, please do not hesitate to contact MMF Protection et Sécurité.

Our experts are on hand to provide you with all the information you need, and to advise you on the product best suited to your requirements