

ROLLIX 6 automatic personal link



ROLLIX 6 Automatic Personal Link

The 2-position ROLLIX 6 Automatic Personal Link is a practical device for managing the unwinding and rewinding of aramid cord. In position 1, it limits unwinding to 1.25 m for precise control. In position 2, the cord is free to unwind up to 6 m without intermediate blocking, ensuring smooth operation. This system guarantees both safety and flexibility, thanks to the strength of the aramid cord, while facilitating use in situations where mobility and responsiveness are essential.

Features :

- 2-position mechanism: unwinding limited to 1.25 m or free up to 6 m
- Automatic full-length rewind without blocking
- 4 mm diameter aramid cord
- Breaking strength: over 200 daN
- High-temperature resistance: up to 500°C
- Fast, tool-free attachment
- Rope change without dismantling the housing
- Weight: 500 g
- Case dimensions: 140 x 120 x 40 mm

Advantages of the ROLLIX 6 automatic personal link

Safety and ease of use: thanks to its automatic rewinding and limited locking system, it prevents unnecessary tension and ensures better rope management.

High strength: the aramid cord ensures optimum resistance to tensile stress and high temperatures.

Easy installation and maintenance: no tools required for fastening, and easy rope replacement without dismantling.

Compact and lightweight: its small footprint makes it easy to transport and install in a variety of environments.

Application:

The ROLLIX 6 Automatic Personal Link is ideal for applications requiring optimized cord management, particularly in the industrial, safety and work-at-height sectors. Its robustness and ease of use make it an indispensable tool for professionals looking for reliability and performance.

The ROLLIX 6 is a high-performance, hard-wearing device designed for intuitive, safe use. Thanks to its automatic rewind mechanism and enhanced strength, it is ideally suited to the most demanding environments.