

## GFR male fitting ring bushing PN25



Product features:

Reference: -  
EAN13: -

Sleeve diameter: 25, 19  
DN GFR: Male 20

### GFR male fitting PN25 brass corrugated sleeve - E 29-579 standard

Opt for reliability and performance with our **GFR male fitting with PN25 brass ring bushing**, compliant with **standard E 29-579**. Designed to meet the requirements of hydraulic and pneumatic installations, this professional-grade fitting ensures optimum sealing and increased resistance to pressure.

Made from **high-quality brass**, the GFR male fitting is ideal for secure connections in water, compressed air or non-corrosive fluid networks. Its **corrugated bushing** guarantees excellent pipe retention, reducing the risk of

leakage even in high-pressure conditions (up to **25 bar - PN25**).

Main features :

- **Type:** GFR male fitting with corrugated bushing
- **Pressure rating:** PN25
- **Material:** Brass
- **Standard:** Conforms to standard **E 29-579**
- **Use:** Water, air and compatible fluid systems
- **Fastening:** Slip-on with optimum tightening

Advantages :

- Corrosion- and wear-resistant
- Quick installation without special tools
- Suitable for industrial and domestic environments
- Reliability and longevity of the connection system
- Whether for a new installation or replacement, the **GFR male PN25 brass fitting** is a durable solution that guarantees a perfect seal in compliance with current standards.