

GFR female fitting with ring bushing PN25



Product features:

Reference: -
EAN13: -

Sleeve diameter: 25
DN GFR: Male 20

GFR female fitting PN25 brass corrugated sleeve - Performance and reliability

Ensure the safety and durability of your installations with our **GFR female ring nut PN25 in brass**. Ideal for high-pressure pipe connections, this fitting guarantees excellent mechanical strength and a perfect seal, even under demanding operating conditions.

In compliance with technical quality standards, this fitting is made from **robust brass**, a material that is resistant to corrosion and wear, and perfectly suited to plumbing, heating and compressed air applications. Thanks to its **corrugated bushing**, it ensures effective hose attachment, limiting the risk of uncoupling or leakage.

Technical specifications :

- **Type:** GFR female fitting with corrugated sleeve
- **Connection:** Female thread
- **Pressure rating:** PN25 (25 bar)
- **Material:** High-strength brass

- **Manufacturing standard:** Conforms to professional standards
- **Application:** Water, air, compatible fluids

Product benefits :

- Reliable sealing up to 25 bar
- Fast, safe installation
- High resistance to temperature and pressure
- Suitable for domestic and industrial installations

The **GFR female ring bushing PN25** is the ideal solution for durable, high-performance installations that meet today's technical requirements. Its precise design makes it an essential component for your hydraulic and pneumatic networks.