

GFR male fitting PN16 male threaded sleeve



Product features:

Reference: -
EAN13: -

Male thread diameter / outlet: 1"
DN GFR: Male 20

GFR male threaded sleeve PN16 in brass - Quality and safety

Choose performance with our **GFR male PN16 brass threaded sleeve fitting**, an essential component for hydraulic or pneumatic installations requiring a reliable connection under moderate pressure. This fitting combines robustness, ease of installation and compliance with professional requirements.

Made from **high-grade brass**, it offers excellent corrosion resistance and guarantees optimum longevity. Its **male threaded connection** ensures a solid mechanical bond, while the **bushing** provides effective hose retention. It's ideal for water, compressed air or other compatible fluid networks.

Key features:

- **Type:** GFR male fitting with sleeve and male thread

- **Pressure rating:** PN16 (16 bar)
- **Material:** Brass
- **Connection:** Standard male thread
- **Application:** Hydraulic, pneumatic and sanitary networks
- **Installation:** Easy and secure

Advantages :

- Fast, solder-free installation
- Pressure resistance up to 16 bar
- Excellent oxidation resistance
- Suitable for domestic and industrial environments

The **GFR male threaded sleeve fitting PN16 in brass** is a reliable, long-lasting solution for ensuring the tightness and strength of your connections in pressurized networks. Designed for easy installation, it integrates perfectly into all your fluid distribution systems.