# Wall-mounted eye and face washer 3868



## Wall-mounted eye and face wash station Krusman 3868 - EN 15154 & ANSI Z358.1 compliant emergency station

### Introducing the Krusman 3868 eye and face washer - Professional eye/face safety device

Visit **Krusman Eyewash 3868** is a wall-mounted eye and face washer designed for rapid, effective intervention after chemical exposure or industrial accidents. Reliable and durable, it complies with European EN 15154-2 and American ANSI/ISEA Z358.1 standards, guaranteeing maximum protection in an emergency.

### Advantages of the 3868 wall-mounted eye and face washer - Performance, sturdiness and simplicity

- **Controlled flow** : about **14 L/min**, with regulated flow and integrated filter on each nozzle.
- **Automatic draining** self-draining ball valve (without spring) to prevent water stagnation.
- **Sustainable materials** : powder-coated stainless steel bowl, brass tap, aluminium wall bracket.
- **Signage included** emergency light panel supplied with each unit.

### Krusman 3868 technical data - Dimensions, pressure, connections

| Features | Detail |
|---|---|
| **Product number** | 3868 |
| **Installation** | Mural |
| **Flow** | ? 14 L/min |
| **Required pressure** | Min. 2.4 bar |
| **Water connection** | ½? female |
| **Drain connection** | 1 ¼? female |
| **Dimensions (W×H×D)** | 380 × 230 × 365 mm |
| **Net weight** | 4 kg |
| **Materials** | Powder-coated stainless steel, brass, aluminum |
| **Accessories included** | Lid, bowl, illuminated panel |

## Installation instructions - Height, connections and testing

- Set at about **1,100 mm** from ground to nozzle level.
- Ensure a water supply ? 14 L/min at 2.4 bar minimum.
- Also connect to a drain via 1 ¼? outlet.
- Perform a function test after installation.

## Safety standards complied with - EN 15154-2 and ANSI/ISEA Z358.1

- Compliance **EN 15154-2** for permanent eyewash units (flow rate, height & duration).
- Compliant **ANSI/ISEA Z358.1** guaranteeing a minimum flow rate (>= 1.5 L/min) for at least 15 minutes.

These standards ensure adequate rinsing for the entire duration required.

## Professional FAQ - Frequently asked questions

**Is this eye and face washer suitable for chemical workshops?**
Yes, it meets EN 15154-2 and ANSI Z358.1 standards, perfectly designed for hazardous environments.

**What supply pressure do I need?**
A pressure of at least **2.4 bar** is required to maintain the flow rate of 14 L/min.

**Is the illuminated sign included?**
Yes, **an illuminated emergency sign** is supplied with each unit.