

# Flashlight PELI™ STEALTHLITE™ 2460Z1 ATEX ZONE 1 rechargeable



## Peli™ 2460Z1 rechargeable ATEX Zone 1 flashlight: safe lighting in hazardous areas

The Peli™ 2460Z1 rechargeable <u>ATEX</u> Zone <u>1 flashlight</u> is a portable LED lighting tool designed specifically for hazardous environments. **Certified explosion-proof to ATEX Zone 1** and waterproof (IPX7), it guarantees safe use in hazardous areas.

With a light output of 181 lumens, this lamp provides highly efficient lighting. Its ergonomic, compact design makes it easy to hold, while its lamp body made of resistant materials ensures shock and corrosion protection.

The **Peli™ 2460Z1** is also equipped with a rechargeable NiMH battery, offering a 5-hour runtime. Its 220V/12V charging base makes recharging quick and easy. All in all, the **Peli™** 2460Z1 **flashlight** is the must-have equipment to guarantee safety and efficiency in hazardous areas.

#### Features:

Here are the main features of the Peli™ 2460Z1 ATEX Zone 1 flashlight:

- **Durable ABS shell**: Robust design for impact and corrosion protection.
- 181 lumen output: Offers optimum brightness for targeting details in the dark.
- Beam range: Up to 181 meters for long-distance illumination.
- 5-hour runtime: Equipped with 4 NiMH batteries for extended runtime.
- Accessories included: Supplied with 220V/12V charger and wrist strap.
- Compact, ergonomic design: Easy to handle, with side switch for convenient use.

#### **Benefits:**

The <u>Peli™</u> 2460Z1 <u>flashlight</u> is an essential tool for professionals working in hazardous environments, such as those exposed to gases and fuels. Thanks to its explosion-proof certification (ATEX Zone 1) and waterproofing (IPX7), it ensures maximum protection and safe use in critical conditions.

Its ergonomic design, with a side switch, makes it easy to activate, even when wearing gloves, while its compactness facilitates transport and storage. With a powerful 181 lumen LED beam, the lamp offers long-range



illumination, perfect for dark areas.

- Enhanced safety: Certified explosion-proof and waterproof for use in hazardous areas.
- Ergonomics: Side-mounted switch for easy handling.
- Robustness: Shock- and corrosion-resistant casing.
- Durable performance: 5-hour autonomy with easy recharging via 220V/12V socket.

### Standards and certifications:

ATEX certification: CE Ex II 2 G Ex ib IIC T4 Gb (gas)

Manufacturer reference: 2460-050-241E

**Customs code**: 85131000

EAN: 19428154547