Universal wrench in non-sparking copper alloy for fittings DN20 to 115



Universal Wrench 3928.782 - non-sparking brass tool for fittings DN 20 to 115

The 3928.782 Universal Wrench is designed to be versatile and robust. Thanks to its wide compatibility range (DN 20 to 115), it can be used on most pipe fittings, half-fittings and dry-columns. Its brass construction guarantees high resistance while remaining non-sparking, which is essential for sensitive environments.

The tool is designed to be compact, easy to handle even when wearing gloves, and sturdy enough to withstand the rigors of the job. Its one-piece design ensures that there are no weak points likely to break during intensive use.

The 3928.782 universal wrench can be used to tighten, loosen and manipulate pipe fittings under standard or

emergency conditions. It is also suitable for applications where spark protection is required.

Benefits & highlights

What sets the 3928.782 apart is its combination of application range, robustness and safety. Its non-sparking material makes it suitable for use in high-risk environments, and its DN 20 - 115 compatibility makes it highly versatile. Its format is designed to be transportable in intervention equipment and quickly usable in the field.

Recommended uses

This wrench is particularly useful for firefighters, water and sewerage operators, dry column technicians, fire maintenance services and any team working on piping networks. It can be used for maintenance, repairs and testing on existing installations.

Compatibility & functions

The 3928.782 Universal Tricoise Wrench covers the DN 20 to DN 115 range, corresponding to the fittings most commonly used in water distribution, firefighting and sprinkler systems. It is compatible with conventional half-fittings and building dry columns. It incorporates a head adapted to standard connection parts in hydraulic and fire-fighting systems.

FAQ - Frequently asked questions

What material is used? The wrench is made of non-sparking brass, guaranteeing safety and durability.

What fitting range does it cover? It is designed for fittings from DN 20 to DN 115.

Is it suitable for environments where there is a risk of sparking? Yes, thanks to its non-sparking brass construction.

Can it be used with gloves? Yes, its design makes it easy to handle even with protective gloves.

How long does it last? The sturdy one-piece construction gives it excellent durability in intensive use.

Why choose the 3928.782 Universal Spanner?

The 3928.782 wrench offers a reliable, versatile and safe solution for work on hydraulic, fire and water distribution networks. Its DN 20 to 115 compatibility, non-sparking material and solid construction make it a trusted tool for professionals. Include it in your intervention kit and make sure you have the right tool for your infrastructure's fittings.