Peacock tail water curtain from 60 to 200L/min with DSP45 connection without lock



60 to 200 L/min peacock tail water curtain with DSP45 symmetrical connection without lock

The **60 to 200 L/min peacock tail water curtain with DSP45 symmetrical connection** is an essential piece of equipment for fire-fighting and protection of sensitive areas. Designed to generate a wide, homogeneous screen of water, it creates an effective thermal barrier to limit the spread of flames and protect responders.

Equipped with a **DSP45 symmetrical, lock-free coupling**, it ensures fast, reliable connection to standardized fire hoses, making it easy to install in the field.

Fire water curtain with adjustable flow rate 60 to 200 L/min

Thanks to its flow rate range from **60 to 200 liters per minute**, this water curtain can be adapted to different operational situations. It allows you to adjust the power of the jet to suit your needs: protecting a facade, containing an outbreak or securing an intervention zone.

Technical specifications

- Type: peacock tail water curtain
- Flow range: **60 to 200 L/min**
- Connection: **symmetrical DSP45**
- Version: without lock
- Wide jet forming a homogeneous water screen
- Quick installation on attack or protection line

DSP45 symmetrical connection without lock

Equipped with a **symmetrical DSP45 connection**, this water curtain is compatible with standard fire-fighting equipment used by emergency services and response teams. The **latchless** version allows quick and easy

handling during operations.

The symmetrical connection facilitates coupling and decoupling, optimizing commissioning time on site.

Peacock tail water curtain applications

Thermal protection

The water curtain creates a protective barrier against radiant heat, particularly useful for protecting structures, tanks or hazardous areas.

Containment and propagation limitation

It helps limit the spread of smoke and flames by creating a continuous screen of water between the fire and the area to be protected.

Professional use

Suitable for fire departments, high-risk industries and sensitive sites, this device meets the requirements of operational interventions requiring reliability and efficiency.

Why choose this DSP45 water curtain?

Choosing this **60 to 200 L/min peacock tail water curtain** means opting for high-performance equipment, compatible with standard DSP45 fittings and designed for rapid installation. Its adjustable flow range and robust design make it an ideal solution for fire protection and securing exposed areas.