

Peacock tail water curtain from 60 to 200L/min with DSP45 connection with lock



Peacock tail water curtain 60 to 200 L/min with DSP45 connection and lock

The **60 to 200 L/min peacock tail water curtain with DSP45 connection and lock** is designed for fire protection and securing areas exposed to radiant heat. It generates a wide, homogeneous screen of water to create an effective thermal barrier and limit the spread of flames.

Equipped with a **symmetrical DSP45 coupling with lock**, this model guarantees a secure connection to standardized fire hoses, ensuring a reliable hold even under pressure.

Adjustable-flow fire water curtain 60 to 200 L/min

Thanks to its adjustable flow range from **60 to 200 liters per minute**, this water curtain can be adapted to different operational situations. The volume of water can be adjusted to suit the level of protection required: containment of an outbreak, protection of a facade or securing an intervention zone.

Technical specifications

- Type: peacock tail water curtain
- Flow range: **60 to 200 L/min**
- Connection: **symmetrical DSP45**
- Version: **with safety lock**
- Wide, homogeneous water screen projection
- Quick to install on a fire line

DSP45 fitting with lock: enhanced safety

The **DSP45 symmetrical fitting with lock** ensures reliable, secure attachment to the fire-fighting system. The locking system limits the risk of accidental disconnection during operation, guaranteeing continuity of water

supply.

This configuration is particularly suited to demanding environments and operations requiring maximum safety.

Peacock tail water curtain applications

Thermal protection of structures

The water curtain forms a barrier against radiant heat, protecting buildings, tanks, industrial installations and sensitive areas.

Smoke and flame containment

By creating a continuous screen of water, it helps to limit the spread of fire and ensure the safety of fire-fighting teams.

Intensive professional use

Suitable for fire departments, industrial sites, classified installations and high-risk environments, this water curtain meets the most stringent operational requirements.

Why choose this DSP45 water curtain with lock?

Choosing this **60 to 200 L/min peacock tail water curtain with lock** means opting for high-performance, reliable and safe equipment. Its adjustable flow range and lockable DSP45 connection guarantee optimum protection during fire-fighting operations.