

Half-coupling without lock female aluminum threaded sleeve



Half coupling without lock female threaded sleeve aluminum

The **Guillemin aluminum half-fitting** is an essential component for fluid transfer installations. Compliant with **NF E 29-572** and **EN 14420-8** standards, this lockless half-fitting provides a reliable, secure connection for various types of hydraulic and industrial circuits. Its robust design and female threaded bushing make it a preferred choice for many applications.

Features :

Material: High-strength aluminum Standards: NF E 29-572 / EN 14420-8 Type: Guillemin half coupling without lock Connection: Female threaded sleeve Pressure rating: PN16 Use: Compatible with various industrial liquids and pumping solutions

Advantages of a lockless half-fitting with female aluminum threaded sleeve :

Reliability and safety: Compliant with current standards, this fitting guarantees optimum tightness.
Robust material: Aluminum offers excellent resistance to impact and corrosion.
Easy installation: The threaded sleeve connection enables fast, efficient assembly.
Adaptability: Compatible with many industrial fluid transfer systems.

Application:

The Guillemin half-fitting is used in many industrial sectors, including:

- Transport and distribution of liquids: water, chemicals, hydrocarbons, etc.
- Food and chemical industry: Compliance with current safety standards.
- Oil and agriculture: Ideal for pumping and storage solutions.

Choosing the **Guillemin NF E 29-572 PN16 and EN 14420-8 aluminum fitting** means choosing a reliable, longlasting product that complies with industrial requirements. **MMF Protection et Sécurité** offers you this product with personalized support.



? Need more information? Contact MMF Protection et Sécurité for a quote or advice tailored to your needs.

MMF PROTECTION ET SÉCURITÉ - 672 RUE DES MERCIÈRES - PARC DES MERCIÈRES - 69140 RILLIEUX LA PAPE - FRANCE Tél. 04 78 00 00 25 - Fax 04 78 00 96 61 - www.mmf.fr - e-mail : mmf@mmf.fr

Siret : 79587045000041 - APE : 4669B - RCS : RCS LYON B 795870450 - N° TVA intracom : FR12795870450 - Capital : 211 200,00 €