

## Headlamp PELI™ 2755Z0 Atex Zone 0



### Peli™ 2755Z0 ATEX Zone 0 headlamp - Safe lighting for hazardous environments

Discover the [Peli™ ATEX Zone 0 headlamp](#) from our professional lighting range. The **Peli™ 2755Z0 headlamp** is specially designed to comply with the strictest **ATEX** standards, including **Zone 0 (Category 1)**. This **ATEX headlamp** is equipped with a fabric strap, a rubber strap and a helmet mounting bracket, guaranteeing safe and comfortable wear in all situations.

The body of the **Peli™ 2755Z0 ATEX headlamp** can be rotated 45 degrees, providing optimum illumination. In the upright position, each LED illuminates effectively downwards. Lightweight at just 96 g, this **Peli™ headlamp** offers **3 lighting modes** to suit different needs. It has a battery life of up to 16 hours.

#### ATEX Zone 0 Peli™ LED 2755Z0 headlamp features:

The **ATEX Zone 0 Peli™ LED 2755Z0 headlamp** meets the needs of professionals operating in demanding environments. **ATEX Zone 0** certified, it guarantees maximum safety in compliance with the latest **ATEX** directive. Made from waterproof (**IP54**) and impact-resistant polymer, this **Peli™ headlamp** ensures exceptional durability even in the harshest conditions.

#### Advantages of the ATEX Zone 0 Peli™ LED 2755Z0 headlamp:

- Powerful LED lighting:** The **ATEX Zone 0 Peli™ 2755Z0 headlamp** delivers a stable beam of light with a maximum intensity of 115 lumens and a range of 61 meters.
- Lighting modes:** It offers **3 lighting modes**, including a flashing mode for improved visibility in **ATEX** environments.
- Autonomy and battery indicator:** Depending on the mode used, this **Peli™ lamp** offers an autonomy ranging from 8 to 16 hours, with an autonomy indicator to track the remaining lighting time.
- Lightweight and comfortable:** Weighing just 96 g (batteries included), the **ATEX Peli™ headlamp** allows extended wear without discomfort.

In emergency services, and rescue for example, where environments can be highly explosive, ATEX compliance

is crucial.

The ATEX Zone 0-certified **Peli™ 2755Z0 headlamp** delivers a stable beam of light with a maximum intensity of 115 lumens during nighttime interventions in burning buildings or during rescues, this lighting power enables firefighters to clearly see hazards and assess the situation, ensuring the safety of crews and victims. What's more, it offers 3 lighting modes: in an emergency, the flashing mode can be used to signal a danger zone to other responders, facilitating coordination during rescue operations.

Depending on the mode used, the lamp has an operating time ranging from 8 to 16 hours, with a battery life indicator to monitor the remaining lighting time. Weighing just 96 g (including batteries), the lamp can be worn for long periods without discomfort. Firefighters already wearing heavy equipment will appreciate the lightness of the lamp, enabling them to work efficiently without adding fatigue, which is essential during intense physical operations.

#### **Contents of the Peli™ ATEX 2755Z0 headlamp:**

- 1 fabric headband
- 1 rubber headband
- 1 adhesive helmet holder
- 3 LR03 batteries

#### **Certification and standards:**

- **ATEX certification:** CE Ex II 1 G Ex ia op is IIC T4 Ga (gas)
- **Product reference:** 027550-0104-241E
- **Customs code:** 85131000
- **EAN:** 19428178611